

L CP 24-12



Lead-acid AGM battery charger

- * *Battery monitoring*
- * *Medical approved*
- * *State of the art design*

Nominal voltage	24 V	
Battery capacity	50 - 125 Ah	
Maximum charging current	12 A	
Output connector	XLR connector (3-pin plug)	
Input voltage	220-240V	
Features	Polarity, Output voltage, Over temperature protection, Active fan for cooling	
Regulation	CE (LVD, EMC, RoHS)	
Standards	EN60335-2-29, EN12184 ISO7176-14, EN60601-1-2	
Dimensions	length	210 mm
	width	175 mm
	height	65 mm
Approx. Weight	0.95 kg	
Packing	1 pc/box	

Typical applications:

- Electric Vehicle
- Electric Wheelchairs
- E-bike
- Lawn mowers
- Golf-Carts
- Medical Equipment
- Recreational vehicles

- Lead-acid battery charger (AGM-Gel)
- Indoor use
- 3-step charger
- High efficient > 90% at full load and 230Vac

LED indication overview:

Orange LED	Green LED	Description:
Off	Off	Battery charger not connected to the mains.
Blinking	Off	1: Battery charger connected to the mains and no battery connected. 2: Battery charger connected to the mains and the connected battery is full.
On	Off	The battery is charging.
Off	On	The battery is full.
Blinking	Blinking	A problem occurred. See chapter "Problem solving"