



LEAD ACID BATTERIES FOR CYCLIC USE

HZB 225-6 EV



- Valve Regulated Maintenance Free
- Analytical Grade electrolyte
- Deep discharge resistant
- Low self discharge
- Built to comply with IEC 896-2, DIN 43534, BS 6290 Pt4, Eurobat.



Nominal Voltage	12 V DC
Nominal Capacity:	
20hr.	226 Ah
10hr.	206 Ah
Internal resistance	1.2mΩ
Max. charge current	0.25CA (60A)
Operation temperature range	
Charge	-15 degr. ~ 40 degr.
Discharge	-20 degr. ~ 60 degr.
Storage temperature	-15 degr. ~ 40 degr.
Fast Charge / Floating charge	7.2V / 6.9 V (±0,15 V)
Cycle life	
100% D.O.D.	270 cycles
75% D.O.D.	350 cycles
50% D.O.D.	550 cycles
Standard terminal	Inserted M8
Housing material	ABS
Dimensions (LxWxH)	243 x 188 x 276mm (±1mm)
Weight	33.8kg.

Can be operated, charged or stored in any position without leakage.

Can not be charged while the terminal is downward.

WWW.INTERCEL.NL



InterceI Energie BV
 Waarderveldweg 3
 2031 BK Haarlem, The Netherlands

Tel +31 23 5149900
 Fax +31 23 5322583
 E-mail: sales@intercel.nl